

POS PRINTER



LK-TE321 / LK-TE322 / LK-TL323
LK-TL320

- Energy star qualified for power efficiency
- High speed printing : 160mm/sec (TE321/TL320)
200mm/sec(TE322), 300mm/sec (TE323)
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Various O/S drivers : Windows printer driver(2000, XP, 2003, Vista, 7)
WEPOS, OPOS, Linux, Java POS

APPLICATIONS



Shopping



Mart



Airport



Hospital



Coffee Shop



Bank



Restaurant



Ticketing



Parking



Lottery




Election



EASY-LOAD DESKTOP THERMAL POS PRINTER

LK-TE321 / LK-TE322 / LK-TL323 / LK-TL320



MODEL		LK-TE321	LK-TE322	LK-TE323	LK-TL320
PRINTING	METHOD	Direct Thermal			
	SPEED	Max. 160mm/sec	Max. 200mm/sec	Max. 300mm/sec	Max. 160mm/sec
	WIDTH	72mm(512 Dots/Line)			
	RESOLUTION	180DPI			
PAPER	TYPE	Thermal Paper			
	WIDTH	50mm ~ 82.5mm			
	THICKNESS	0.06mm ~ 0.09mm			
	ROLL DIAMETER	Max. \varnothing 80.0mm			
	ROLL CORE INNER	12.5mm \pm 0.5mm			
RELIABILITY	TPH LIFE	160km			
	MCBF	60,000,000Lines			
AUTO CUTTER		1,500,000cuts(Guillotine)			
SENSOR	STANDARD	Paper End, Paper Low, Cover Open			
	OPTION	Black Mark Sensor			
INTERFACE		USB (B type) plus one more card selectable (Serial, Parallel, Wi-Fi, ethernet)			USB (B type) + Serial Build-in
EMULATION		ESC/POS Command Compatible			
DRIVER		Windows Printer Driver(7, XP, 2000, 2003, VISTA), WEPOS, OPOS, Linux, JavaPOS			
POWER	TYPE	External SMPS			
	AC	100 ~ 240Vac 50/60 Hz			
	DC	24Vdc / 1.75A			
TEMPERATURE	OPERATION	5 ~ 40°C			
	STORAGE	-20 ~ 60°C			
DIMENSION		152 x 202 x 150.5 mm (W x D x H)			
WEIGHT		1.7kg			
COLOR		Cool grey, Ivory			

INTERFACE



ACCESSORY



Melody box



SEWOO TECH Co., Ltd.

374-2, Gajang-dong, Osan-si, Gyeonggi-do, 447-210, Korea
 T. +82-31-459-8200 F. +82-31-459-8880
 www.miniprnter.com

